




- NOTE:
1. Rating : DC 5V 10mA
  2. Contact Resistance: 100mΩMAX
  3. Insulation Resistance: 100MΩMIN
  4. Soldering Temper: 260±5°/5s
  5. Mechanical Life: 100,000 cycles
  6. Ever Portion 80 ± 50 gf
  7. Push Portion 205 ± 80 gf
  8. Travel: -24° 0° +24°

A向24° a与b

B向24° a与d

C向150g  
a与c通



ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑤	Spring	—	1	SUS	Natural	—
④	Terminal	—	5	Phosphor Bronze	Plating silver	—
③	Cover	—	1	SUS	Natural	—
②	Base	—	1	LCP	Black	—
①	Keystroke	—	1	PPA	Black	—
APPROVALS				DATE	REMARK	
DRAWN KUN.LU				2013/8/8	ELECTRONICS CO.,LTD	
CHECKED				TITLE: MULTIFUNCTIONAL SWITCHS		
APPROVALS				PART NO. K1-1502SA-04		
TOLERANCES ARE				30~12.5 ±	±0.30	PROJ:
				10~30 ±	±0.20	
				5~10 ±	±0.15	SHEET 1 OF 1
				~5 ±	±0.10	
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			