



Circuit Diagram

NOTE:
 1. Rating: AC125V 5A/250V 3A
 2. Operating force: 100±30gf
 3. Mechanical Life: 100,000
 3. Electrical Life: 6000—10,000

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑧	Shrapnel 2	—	1	Copper Alloy	—	—
⑦	Shrapnel 1	—	1	Beryllium Copper	—	—
⑥	Contact	—	1	Copper Alloy	Plating silver	—
⑤	Aluminium rivet	—	1	Aluminium Alloy	—	—
④	Terminal	—	3	Copper Alloy	Plating silver	—
③	Housing	—	1	PBT	Black	—
②	Knob	—	1	PBT	Black	—
①	Cover	—	1	PBT	Black	—

APPROVALS	DATE	TITLE
DRAWN J.X.Zhang	2014/8/19	ELECTRONICS CO.,LTD
CHECKED		MICRO SWITCHS
APPROVALS		PART NO. K9-1910B

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	ANGLE	UNIT:	SCALE:	PROD.	SHEET
	A		NEW				30~0.1±	±0.30	mm	1:1	PROJ.	1 OF 1
							10~20	±0.25				
							5~10	±0.20				
							~ 5	±2'				



ELECTRONICS CO.,LTD

MICRO SWITCHS

PART NO. K9-1910B

PROD. SHEET 1 OF 1