



SPECIFICATIONS:

- Voltage Rating: 250V AC Min
- Current Rating: 2.0A Min
- Dielectric Strength: 1000V AC For 1Minute
- Insulation Resistance: 1000Megohms Min
- Contact Resistance: 30Milliohms Max
- Operation Temperature: -55°C To +125°C
- Product Withstanding Reflow Soldering: 260°C For 15s
- Durability :5000 Cycles
- Normal Force At Working Position: 80g Min
- Insertion Force:>3N
- Insulator: High Temperature Thermoplastic
- UL 94V-0 Black (LCP Black)
- Contact: Beryllium Copper,
- Gold Flash Over Nickel

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
②	Terminal	—	5	Phosphor Bronze	Au Plated	—
①	Housing	—	1	LCP	Black	—

APPROVALS	DATE	TITLE:
DRAWN xu qi feng	2014.12.04	电池座 3P
HRONICS ELECTRONICS CO.,LTD		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
—	A	—	NEW	—	—	—
APPROVALS			PART NO.	BC-4-3P	PROJ:	—
TOLERANCES ARE			UNIT: mm	SCALE: 1:1	DRAWING NO.	SHEET 1 OF 1
30±0.15	±0.30	ANGLE	—	—	—	—
10~30	±0.25	—	—	—	—	—
5~10	±0.20	±2°	—	—	—	—
~5	±0.15	—	—	—	—	—